



# 5 ports Industrial switch FL605G series

## ❖ Overview

The FL605G is a 5-port industrial switch that supports up to 5\*10/100/1000M RJ45 ports;

It supports relay alarm for power off, network broken.

It has a high anti-interference ability, the product supports 6KV surge protection, and 8KV contact / 15KV air ESD protection.

It supports Din-rail installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

## ❖ Pictures



## ❖ Features

- ❖ With 5\*10/100/1000M RJ45 ports;
- ❖ Supports relay alarm for power off, network broken;
- ❖ Supports 6KV surge protection, 8KV contact / 15KV air ESD protection;
- ❖ Supports working temperature  $-40^{\circ}\text{C} \sim 75^{\circ}\text{C}$ ;
- ❖ Supports Din-rail installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

Telefly Telecommunications Equipment Co., Ltd

Email:telefly-tyler@telefly.cn Tel: (+86 755) 8607 0094 Fax: (+86 755) 8607 0000 Web:<https://www.telefly.cn/>

ADD: 96 Building, the second industrial area, Gongming, Baoan District, Shenzhen, Guangdong Province, P.R.China



## 5 ports Industrial switch FL605G series

### ❖ Specifications

Parameter	Specifications
Power supply	Powered by power adaptor
Range of voltage	DC 9~56V
Consumption	Self consumption<5W
Ethernet ports	Ports 1~5: 10/100/1000Base-T ports
Cable and distance	Use cat5e/6,100m max
Standard	IEEE802.3, IEEE802.3u, IEEE802.3z
Switch fabric	10 Gbps
Though put	7.4 Mpps
Buffer	1M
MAC address table	8K
Indicator	Power: 2 *red ; Ethernet ports 1~6: Green LEDs and yellow LEDs indicate Link/Act
Protection	Surge: 6KV, standard: IEC61000-4-5 ESD: 8KV: contact / 15KV: air, standard:IEC61000-4-2
Working temperature	-40℃~75℃
Storage temperature	-40℃~85℃
Humidity	0~95%(No condensation)
Dimension(L×W×H)	120×90×35 mm
Material	Aluminum
Colour	Black
Net-weight	350g

### ❖ Order information

Model	Description
FL605G	With 5*10/100/1000M RJ45 ports; 2*DC 9-56V power supply; Supports relay alarm function for power off, network broken; -40~75℃.

Telefly Telecommunications Equipment Co., Ltd

Email:telefly-tyler@telefly.cn Tel: (+86 755) 8607 0094 Fax: (+86 755) 8607 0000 Web:<https://www.telefly.cn/>

ADD: 96 Building, the second industrial area, Gongming, Baoan District, Shenzhen, Guangdong Province, P.R.China