



TELEFLY

8 ports Industrial switch FL608G series

❖ Overview

The FL608G is a 8-port industrial switch that supports up to 8 *10/100/1000M RJ45 ports;

It has a high anti-interference ability, the product supports 6KV surge protection, and 8KV contact /15KV air ESD protection;

It supports wall hanging, desktop and Din-rail installation, reliable and durable, and can be used in security network video monitoring, network engineering and other occasions.

❖ Picture



❖ Features

- ❖ With 8*10/100/1000M RJ45 ports;
- ❖ Supports relay alarm for power off, network broken;
- ❖ Supports 6KV surge protection, 8KV contact / 15KV air ESD protection;
- ❖ Supports working temperature -40°C ~75°C.

Telefly Telecommunications Equipment Co., Ltd

Email:telefly-tyler@telefly.cn Tel: (+86 755) 8607 0094 Fax: (+86 755) 8607 0000 Web:<https://www.telefly.cn/>

ADD: 96 Building, the second industrial area, Gongming, Baoan District, Shenzhen, Guangdong Province, P.R.China



8 ports Industrial switch FL608G series

❖ Specifications

| Parameter | Specifications |
|---------------------|--------------------------------------------------------------------------------------------|
| Power supply | Powered by power adaptor |
| Range of voltage | DC 12~54V |
| Consumption | Self consumption<5W |
| Ethernet ports | Ports 1-8: 10/100/1000Base-T ports |
| Cable and distance | Use cat5e/6,100m max |
| Standard | IEEE802.3, IEEE802.3u, IEEE802.3z |
| Switch fabric | 16 Gbps |
| Though put | 11.9 Mpps |
| Buffer | 1M |
| MAC address table | 8K |
| Indicator | Power: 2 *red ; Ethernet ports1~8 : Green LEDs and yellow LEDs indicate Link/Act |
| Protection | Surge: 6KV, standard: IEC61000-4-5 ESD: 8KV: contact / 15KV: air, standard:IEC61000-4-2 |
| Working temperature | -40℃~75℃ |
| Storage temperature | -40℃~85℃ |
| Humidity | 0~95%(No condensation) |
| Dimension(L×W×H) | 138×108×49 mm |
| Material | Aluminum |
| Colour | Black |
| Net-weight | 450g |

❖ Order information

| Model | Description |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FL608G | With 8*10/100/1000M RJ45 ports; 2 *DC 12-54V power supply(Power adaptor buy extra); Supports relay alarm function for power off, network broken; -40~75℃. |

Telefly Telecommunications Equipment Co., Ltd

Email:telefly-tyler@telefly.cn Tel: (+86 755) 8607 0094 Fax: (+86 755) 8607 0000 Web:https://www.telefly.cn/

ADD: 96 Building, the second industrial area, Gongming, Baoan District, Shenzhen, Guangdong Province, P.R.China